

XSF

25 Grand

DOUBLE SOLIDS FLOOR FINISH

DESCRIPTION

A high solids, metal interlock combination floor sealer and long-lasting, clear, acrylic floor finish. Easy to apply with no "mop drag." Levels beautifully and dries to that much desired wet look.

USES

Vinyl, VAT, VCT, rubber, linoleum, marble, terrazzo, concrete, brick, flagstone, epoxy and other resilient and non-resilient floors.

HOW TO USE

PREPARATION: May be applied over other hard, non-wax floor finishes if they are clean and in good condition, but for best results we suggest stripping with our companion stripper. Then rinse thoroughly and allow floor to dry.

APPLICATION: Apply in thin coats. Lay finish in "figure 8" strokes, slightly overlapping each pass. Avoid contact with finish as it dries. Allow each coat to dry 20-30 minutes before applying a next coat or walking on floor.

NOTE: Humid conditions may require longer drying times between coats.

MAINTENANCE: Dust mopping and damp mopping will keep floors bright and shiny. This finish is an excellent base for spray buffing.

BENEFITS

HIGH SOLIDS: The quick answer to building the necessary tough foundation for spray buff floor maintenance.

EASY APPLICATION: Though high in solids, each coat lays down beautifully with no mop drag or streaks.

ALL ACRYLIC: Leaves a perfectly clear, non-yellowing film that won't black mark.

SUPER GLOSS: Dries to a high gloss and maintains its gloss under heavy traffic.

METAL INTERLOCK: In spite of its resistance to water and detergents, 25 Grand can be easily removed with its companion stripper when desired.

SPECIFICATIONS

APPEARANCEMilky liquid
SOLIDS CONTENT25 ± 0.5%
ODORCharacteristic
SPECIFIC GRAVITY.....1.020 ± 0.005
DENSITY.....8.51 ± 0.05 lb/gal
BOILING POINTNear 212°F
pH.....8.5 ± 0.5
FLASH POINTNone to boiling
STABILITYOne year minimum

DISTRIBUTED BY