

C480

Durapol

Commercial Grade • Non-Dulling FLOOR FINISH

DESCRIPTION

This easy to maintain floor polish can be buffed and restored like a wax, but contains no wax and is not slippery like wax. It applies easily and smoothly and dries quickly to a gloss without polishing. When, after heavy traffic, it begins to show wear, light buffing restores its appearance.

USES

Vinyl, VAT, VCT, rubber, linoleum, marble, terrazzo, concrete, brick, flagstone, epoxy and other resilient and non-resilient floors.

HOW TO USE

May be applied over other hard, non-wax finishes. But for assured results, the old brand of polish should be removed, and the new finish applied to a clean, dry floor.

1. Apply finish in "figure 8" strokes that will cover fully, but not so liberally as to run into low spots.
2. Allow to dry completely. Do not re-work finish while it is drying.
3. When dry, an additional coat, or coats, may be applied if needed. Apply each succeeding coat a little less liberally than the previous one.

FUTURE CARE: Remove gritty soil with a damp or treated mop. Use a detergent solution to remove ground-in dirt. Revive dull areas by spray-buffing or by applying finish to worn areas. The thermoplastic properties of Durapol allow it to be buffed at any speed.

BENEFITS

BALANCED HARDNESS: Hard and tough enough to resist scuffing from heavy traffic, but responds to dry buffing, and is an excellent base for spray buffing.

EASY APPLICATION: Every coat goes down effortlessly and smoothly with no mop drag.

SLIP RESISTANT: Meets ASTM standards with James slip test machine.

SELF POLISHING: Dries to a high gloss without polishing and holds its gloss under traffic.

METAL INTERLOCK: In spite of its resistance to water and detergents, Durapol can be easily removed with its companion stripper when desired.

SPECIFICATIONS

APPEARANCEMilky liquid
SOLIDS CONTENT18.0 ± 0.5%
ODORCharacteristic floor finish
SPECIFIC GRAVITY.....1.020 ± 0.005
DENSITY.....8.51 ± 0.05 lb/gal
BOILING POINTNear 212°F
pH.....8.5 ± 0.5
FLASH POINTNone to boiling
STABILITYOne year minimum

DISTRIBUTED BY