

C500

Deep Gloss

FLOOR FINISH For Heavy Traffic Floors

DESCRIPTION

This modern floor finish has been specially formulated to resist dehydration from high speed floor machines. Thus, it also stands up well against wear of heavy foot traffic, and will last longer than other finishes regardless of how it is maintained.

USES

Vinyl, VAT, VCT, rubber, linoleum, marble, terrazzo, concrete, brick, flagstone, epoxy and other resilient and non-resilient floors.

HOW TO USE

May be applied over other hard, non-wax finishes. But for assured results, the old brand of polish should be removed, and the new finish applied to a clean, dry floor.

1. Apply finish in straight, even strokes that will cover fully, but not so liberally as to run into spots.
2. Allow to dry completely. Do not re-work finish while it is drying.
3. When dry, an additional coat, or coats, may be applied if needed. Apply each succeeding coat a little less liberally than the previous one.

The number of coats needed depends on the condition of the floor and the gloss desired. If the floor is to be burnished with a high speed machine, more coats are suggested to keep marks on the surface for easy removal.

BENEFITS

HIGHLY BUFFABLE: Made to be buffable with standard floor machines and/or high speed burnishers without the finish powdering.

EASY APPLICATION: Each new coat levels beautifully with the previous one, without bubbles, streaks or mop drag.

CLEAR & COLORLESS: Dries to a gloss-like clarity that intensifies the natural colors in the floor, not discolor it.

WATER RESISTANT: Completely impervious to spills and to water tracked on the floor during bad weather.

EASILY REMOVED: In spite of its resistance to water and detergents, Deep Gloss can be easily removed with its companion stripper when desired.

SPECIFICATIONS

APPEARANCEMilky liquid
SOLIDS CONTENT22.0 ± 0.5%
ODORCharacteristic
SPECIFIC GRAVITY1.020 ± 0.005
DENSITY.....8.51 ± 0.05 lb/gal
BOILING POINTNear 212°F
pH.....8.5 ± 0.5
FLASH POINTNone to boiling
STABILITYOne year minimum

DISTRIBUTED BY