



Product Description

Revolutionary, Cutting Edge Technology

CreteClean Plus with Scar Guard™ is uniquely formulated to clean and condition densified and densified-polished concrete, as well as all hard surface floors (other than natural wood). Proprietary Polar Micelle Technology pulls contaminants out and up from the concrete and holds it in suspension, providing maximum cleaning efficiency.

Reduced Environmental Impact

Due to its high concentration, less product is required for use, and therefore less needs to be purchased, shipped, and stored, greatly reducing its overall environmental impact.

Improves Floor Performance

The chemically advanced technology of CreteClean Plus with Scar Guard elevates it from a detergent to a performance enhancing cleaning agent. Regular and frequent use of CreteClean Plus with Scar Guard can, over time:

- + Help maintain the sheen of densified concrete surfaces,
- + Decrease the visibility of minor scratches and blemishes,
- + Decrease porosity, and
- + Help strengthen and harden concrete surfaces.

Suitable for Use in Food Handling Establishments

CreteClean Plus with Scar Guard is NSF certified and approved for use in institutional, industrial and food handling establishments.

Directions for Use

General Cleaning

CreteClean Plus with Scar Guard is simple and easy to use. First, remove any debris from the area to be cleaned. CreteClean Plus can then be applied by wet mop, automatic scrubber or other means (if using a wet mop, use only a cotton mop head and change the cleaning solution every 800-1,000 ft²). Remove any excess diluted CreteClean Plus and allow the concrete surface to air-dry. For enhanced results on concrete that has been treated with the Ashford Formula™ or RetroPlate® System, periodically burnish or buff the surface with a non-aggressive pad or polishing pad.

Distributed by:



Dilution Ratios

1 oz CreteClean Plus with Scar Guard	1 gal Water	7.8 mL CreteClean Plus with Scar Guard	1 L Water
--	----------------	--	--------------

Technical Info

Form:	Clear, Green Liquid with Fresh Scent Weighs 8.5 lbs / gal (1.02 kg / L)
Flashpoint:	Not Applicable
Freezing:	If product freezes, agitate to re-emulsify
pH:	11.2 [+/- 0.5] (Concentrate) 9-10 (Diluted for Use)
Packaging:	55 gal (208 L) Drums 5 gal (19 L) Pails 1 gal (3.79 L) Jugs
Storage Life & Temp:	Two (2) Years 40°F - 80°F
Dilution Ratio:	General Cleaning: 1 oz CreteClean Plus / gal of H ₂ O (7.8 mL / L) Poultice Cleaning: 4 oz CreteClean Plus / gal of H ₂ O (31.2-39 mL / L)

Poultice Cleaning Procedure for Severe Oil Staining

Remove all loose soil and fine grit. Mop down CreteClean Plus with Scar Guard diluted at 4 oz. / gal of water (31.2-39 mL / L). Agitate the solution to assist the product in penetrating the soil's surface. Cover the wet surface with plastic film and tape down edges. Allow area to remain wet for 10-15 minutes or longer if possible. Remove the plastic film and dispose of soiled solution. The procedure may need to be repeated if soil leaches back to the surface as the concrete completely dries out.

Note: This procedure is designed for spot removal of significant oil or grease staining.

Special Considerations

- Frequency of cleaning depends on the type and quantity of soilage. Contact Curecrete to create a Standard Cleaning Procedure (SCP) for your floor(s).
- The phrase "all hard surfaces" DOES NOT include wood. Wood flexes and creates cracks in the urethane, allowing water to seep through those cracks and penetrate the wood.
- Can be used on floors with paint.
- Several applications of CreteClean Plus with Scar Guard may be needed to remove oil stains from concrete surfaces that have severe oil staining. Additional treatment with an oil emulsifier, such as CreteStrip™, may be necessary.
*CreteStrip is manufactured exclusively by Curecrete.
- Acids, salts, deicers and other harmful substances should be promptly removed to avoid damage to your floor. A proper, regular and frequent maintenance program is highly recommended. Making CreteClean Plus a regular part of your maintenance program will ensure superior results.

Extended Manufacturer Warranty

Due to the superior performance achieved by regularly using CreteClean Plus with Scar Guard, concrete surfaces treated with the Ashford Formula or RetroPlate System can qualify for an extension of their original Manufacturer Warranty to a Lifetime Warranty. Qualifying conditions apply. Contact Curecrete for more information.

Curecrete warrants this product to be free from any manufacturing defects.

Technical Information, Assistance & SDS

NSF Certified

CreteClean Plus with Scar Guard is proud to be NSF Certified, meeting and exceeding strict standards for cleanability, sanitation, and food protection. As a result, CreteClean Plus with Scar Guard is suitable for use in institutional, industrial and food handling establishments.



**Nonfood Compounds
Program Listed - A4
Registration #155552**

Distributed by:



The Bullen Companies

Corporate Headquarters | 1640 Delmar Drive | Folcroft, PA 19032

(610) 534-8900 | fax (610) 534-8912 | www.bullenonline.com